

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁵:

A61M 29/00

A1

(11) International Publication Number:

WO 92/11893

(43) International Publication Date:

23 July 1992 (23.07.92)

(21) International Application Number: PCT/US92/00410

(22) International Filing Date: 14 January 1992 (14.01.92)

(30) Priority data:

640,951

14 January 1991 (14.01.91) US

(71) Applicant: KONTRON INSTRUMENTS, INC. [US/US];
9 Plymouth Street, Everett, MA 02149 (US).(72) Inventors: LOMBARDI, Edward, J.; 48 Lawrence Road,
Derry, NH 03038 (US). HEGARTY, John, M.; 1140
Main Street, Reading, MA 01867 (US). GRIFFIN,
Wayne, P.; 55 Surrey Lane, Dracut, MA 01826 (US).(74) Agent: RZUCIDLO, Eugene, C.; Morgan & Finnegan, 345
Park Avenue, New York, NY 10154 (US).

(81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent).


Published

With international search report.

(54) Title: DURABLE AND FLEXIBLE CATHETER OR CENTRAL LUMEN HAVING A LOW KINK RADIUS

(57) Abstract

An improved durable and flexible catheter (11) or central lumen having good resiliency characteristics and a low kink radius. The catheter or central lumen is an elongated member having an inner layer (22) of a soft elastomeric material and an outer layer (21) of a hard plastic material and is formed by forming the outer layer onto the inner layer by co-extrusion.



DURABLE AND FLEXIBLE CATHETER OR CENTRAL LUMEN
HAVING A LOW KINK RADIUS

BACKGROUND OF THE INVENTION

Intra-aortic balloon (hereinafter IAB) apparatus, more particularly percentaneous IAB apparatus
5 are now widely used for intra-aortic balloon pumping in cardiogenic shock due to acute infarction, post-operative severe low cardiac output state, or inability to wean from cardiopulmonary bypass, refractory unstable angina in the period before and after infarction, recurrent
10 life-threatening tachyarrhythmias, and preoperative support in the present of severe left ventricular dysfunction. Additionally, intra-aortic balloon pumping has been used both experimentally and clinically to reduce infarct size. Such devices have been disclosed in
15 U.S. 4,362,150, the disclosure of which is incorporated, in toto, herein.

One method of inserting an IAB into a patient is via a non-surgical insertion of the device through the femoral artery of the patient. This is the so-called
20 Seldinger technique.

After insertion of the balloon catheter into the patient's femoral artery, the device must be fed through the patient's arterial system until the IAB is correctly positioned for use, usually before the
25 subclavian artery.

This insertion process can induce trauma to the walls of the patient's arterial or venous system. A problem attendant with the insertion procedure occurs in maneuvering the device along the arterial route which may
30 require the twisting and turning of the device.

Trauma can be minimized by providing a flexible IAB which bends in conformance with the passageways. However, there must also be a balance of flexibility and

- 2 -

remains and to prevent or avoid kinking.

Although flexible IAB's have been commercially available for some time, there have been numerous occurrences of central lumen failures in IAB's. Prior art central lumen include a tube made from a single homogeneous plastic while other prior art IAB's have employed a central lumen having a metal coil embedded within the wall of a plastic tube of a single homogeneous plastic material.

These and similar problems have arisen with devices which are inserted into a patient's arterial or venous system and which need to be maneuvered through the system.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved catheter that is particularly well suited for insertion into a patient's arterial.

A further objective is to provide a durable and flexible catheter for use in an IAB or other apparatus in which a catheter is inserted into a patient's arterial system and guided therethrough.

A still further objective is to provide a catheter having a low kink radius and whose flexibility facilitates insertion of the catheter and the guiding of the catheter through tortuous arteries.

A yet further objection of the present invention is to provide a catheter which because of the low kink radius has especially good resiliency characteristics.

To achieve the foregoing and other objectives and in accordance with the purpose of the present invention, a catheter or central lumen is formed which is an elongated hollow member formed of an inner layer and

- 3 -

an outer layer each said layer being composed of a different material and each material having its own unique chemical and physical properties. The inner layer is comprised of a soft elastomeric plastic material that
5 imparts flexibility to the tubing. The outer layer is comprised of a hard plastic material which imparts structural support to the elongated hollow member (whether or central lumen). The combination of these two materials in a single member results in a very durable
10 and flexible structure, exhibiting a low kink radius. Nontoxicity is achieved through the proper selection of layer materials.

Additionally, because of the low kink radius a central lumen according to the present invention has
15 especially good resiliency characteristics. Resiliency is the restoring force which allows the central lumen to return to its original condition after, for example, a kink arises either intentionally or unintentionally during use. In the case of an IAB having a central
20 lumen, if a kink arises, the resiliency characteristics of a central lumen according to the present invention allows the restoration to its original condition, i.e., without the kink, more quickly and more efficiently than in prior art devices.

25 The central lumen of the present invention is applicable to all sizes and types of double lumen IAB devices and is not limited by IAB insertion technique. It may be incorporated into IAB devices intended for insertion by the convention Seldinger technique,
30 Sheathless technique or those techniques incorporating a tear away sheath.

In addition, the catheter or central lumen of the present invention can be used in any utility where a flexible catheter or central lumen is employed, more

specifically in angioplasty, as a pulmonary artery balloon catheter, for antegrade thoracic insertion, or for catheters used with pancreatic or gall bladder problems.

5 The elongated hollow member of the present invention can be produced by any suitable technique which is familiar to those skilled in this art. A preferred technique is a coextrusion process. In the coextrusion process, the outer layer is formed over the inner layer
10 using an extruder and suitable dies.

 The inner layer in order to impart flexibility to the overall structure is made from a non-toxic material comprised of a soft elastomeric material. Such materials are well-known to those skilled in the art.
15 Among some useful materials are polyvinyl chloride, silicone resins and polyurethanes. A preferred group of soft elastomeric plastic materials are polyurethanes. Pellethane 2363-65D, a polyether/polytetramethylene glycol polyurethane sold by Dow Chemicals, U.S.A. is an
20 example of a useful polyurethane.

 The outer layer in order to impart structural support to the present catheter is made from a non-toxic material comprised of a hard plastic material. Such materials are well-known to those familiar with the
25 present pertinent art area and include, polyethylene, polypropylene, polycarbonates, polysulfones, polymethylmethacrylates and nylons. A preferred group of hard plastic materials include the nylons and more preferable the hard plastic material is nylon 6.

30 In a preferred configuration, the catheter or central lumen of the present invention has a tubular configuration in which the inner and outer layers have constant diameters. Normally, the thickness of the outer layer is greater than the thickness of the inner layer.

SUBSTITUTE SHEET

- 5 -

However, these thicknesses may be varied depending upon the application and the end result sought to be achieved. It is also possible that the diameters of the inner and outer layers may be variable either individually or
5 together.

BRIEF DESCRIPTION OF THE DRAWING

The features of the present invention that are believed to be novel are set forth with particularity in
10 the appended claims. The invention, together with further objects and advantages thereof, may best be understood by reference to the following description taken in conjunction with the accompanying drawings in which:

15 Fig. 1 is a cut-away side elevation of the partial structure of an IAB in accordance with the invention.

Fig. 2 is a cut-away side elevation of a tubular member according to the invention.

20 Fig. 3 is a cut-away front elevation of a tubular member according to the invention.

DETAIL DESCRIPTION OF THE DRAWINGS

As shown in Fig. 1, a balloon catheter
25 according to the invention includes a conventional single-chamber intra-aortic balloon 11 and a catheter 12 having disposed within in a elongated member or central lumen 13 which is more fully shown in Fig. 2 and Fig. 3 and described herein below. The balloon is illustrated
30 by way of example as a conventional single chamber IAB.

The balloon 11 is preferably formed of an anti-thrombogenic flexible material and at its proximate end is bonded in fluid-tight manner to an end of catheter 12 and is bonded at its distal end to the flexible end 14 and

SUBSTITUTE SHEET

elongated member or central lumen 13. Additionally, a metal ring 16 may be provided to make the balloon more easily insible to facilitate location of the balloon. Tip 15 is sealably bonded to the distal end of the
5 balloon.

Figures 2 and 3 show side and front elevations of elongated member or central lumen 13 of figure 1. Inner layer 22 is comprised of a soft elastomeric plastic material onto which has been coextruded the outer layer
10 21. Outer layer 21 is comprised of a hard plastic material.

Although only one embodiment of the present invention has been described in detail, it should be understood that the present invention may be embodied in
15 many other specific forms without departing from the spirit or scope of the invention.

A inner layer in tubular form of polyurethane (Pellethane 2363-65D) was prepared and a layer of nylon was formed over the polyurethane tubular layer by co-
20 extrusion. This tubular material was useful as the central lumen in an IAB device and had a kink radius which is about one third that of the central lumen of typical prior art flexible balloon catheters.

The description of the preferred embodiment of
25 the present invention is considered to be illustrative and not restrictive and the invention is not limited to the details given herein, but may be modified within the scope of the appended claims.

SUBSTITUTE SHEET

- 7 -

We claim:

1. In a balloon catheter apparatus including a hollow catheter and an inflatable and deflatable balloon having a proximate end and a distal end, said
5 proximate end of the balloon being sealable attached to an end of said hollow catheter and an elongated member which is disposed within said hollow catheter and extends the length of said catheter into the balloon, the improvement wherein the elongated member is hollow and is
10 comprised of an inner layer and an outer layer wherein the inner layer is comprised of a soft elastomeric material and the outer layer is comprised of a hard plastic material.
2. An apparatus according to claim 1, wherein
15 the elongated member is formed by forming the outer layer onto the inner layer by coextrusion.
3. An apparatus according to claim 1, wherein the inner layer of the elongated member is non-toxic.
4. An apparatus according to claim 1, wherein
20 the outer layer of the elongated member is non-toxic.
5. An apparatus according to claim 1, wherein the inner layer of the elongated member is a polyurethane resin.
6. An apparatus according to claim 1, wherein
25 the outer layer of the elongated member is a nylon.
7. An apparatus according to claim 6, wherein the nylon is nylon 6.
8. An apparatus according to claim 1, wherein the inner layer of the elongated member is polyurethane
30 and the outer layer is nylon.
9. An apparatus according to claim 1, wherein the elongated member exhibits good resiliency characteristics.
10. An intravascular catheter comprising a

SUBSTITUTE SHEET

tubular body formed with an inner layer and an outer layer the inner layer being made of a material comprising a soft elastomeric plastic material and the outer layer being made of a material comprising a hard plastic material the catheter being durable and flexible and having a low kink radius.

11. A catheter according to claim 10, wherein the inner layer is non-toxic.

12. A catheter according to claim 10, wherein the outer layer is non-toxic.

13. A catheter according to claim 10, wherein the outer layer is nylon.

14. A catheter according to claim 13, wherein the outer layer is nylon 6.

15. A catheter according to claim 10, wherein the inner layer is polyurethane.

16. A catheter according to claim 10, wherein the inner layer is polyurethane and the outer layer is nylon.

17. A catheter according to claim 10, wherein the catheter exhibits good resiliency characteristics.

SUBSTITUTE SHEET




FIG. 1




FIG. 2




FIG. 3

SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US92/00410

I. CLASSIFICATION OF SUBJECT MATTER (In several classification systems, indicate only 1)

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC (5): A61M 29/00

II. FIELDS SEARCHED

Minimum Documentation Searched

Classification System

Classification Symbols

U.S.

604/96,264,280,282
606/192,194
128/137,145,146

Documentation Searched other than Minimum Documentation
to the extent that such Documents are included in the Fields Searched

III. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to:
X	US, A, 4,960,410 (PINCHUK) 02 October 1990 See Figures 3A and 3B, and line 65, column 3 through line 11, column 4.	1-6,8-13, 15-17
X,P	US, A, 5,041,089 (MUELLER ET AL.) 20 August 1991 Note figure 1 with inner layer 22 and outer layer 20.	1-4,6,9-13,17
X	US, A, 4,282,876 (FLYNN) 11 August 1981 Note lines 49-51 of column 6 and lines 61-64 of column 6.	10-13,15-17
Y	US, A, 4,762,589 (AKIYAMA ET AL.) 09 August 1988 Note line 30 column 6.	7 & 14

* Special categories of cited documents: 10

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published on or to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

Date of Mailing of this International Search Report

06 April 1992

04 MAY 1992

International Searching Authority

ISA/US

Signature of Authorized Officer

Anthony M. Gutowski

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.